



# NVIDIA JETSON NANO MODULE

SMALL. POWERFUL. POWERED BY AI.

## Bringing AI to millions of new systems at the edge

The NVIDIA® Jetson Nano™ module is opening amazing new possibilities for edge computing. It delivers up to 472 GFLOPS of accelerated computing, can run many modern neural networks in parallel, and delivers the performance to process data from multiple high-resolution sensors—a requirement for full AI systems. It's also production-ready and supports all popular AI frameworks. This makes Jetson Nano the ideal platform for developing mass market AI products such as AIoT gateways, smart network video recorders and cameras, consumer robots, and optical inspection systems.

The system-on-module is powered by the NVIDIA Maxwell™ GPU with 4 GB of memory, which allows real-time processing of high-resolution inputs. It offers a unique combination of performance, power advantage, and a rich set of IOs, from high-speed CSI and PCIe to low-speed I2Cs and GPIOs. Plus, it supports multiple diverse sets of sensors to enable a variety of applications with incredible power efficiency, consuming as little as 5 W.

Jetson Nano is supported by NVIDIA JetPack™, which includes a board support package (BSP), Linux OS, NVIDIA CUDA®, cuDNN, and TensorRT™ software libraries for deep learning, computer vision, GPU computing, multimedia processing, and much more. The comprehensive software stack makes AI deployment on autonomous machines fast, reduces complexity, and speeds time to market.

The same JetPack SDK is used across the entire NVIDIA Jetson™ family of products and is fully compatible with NVIDIA's world-leading AI platform for training and deploying AI software.

## KEY FEATURES

### Jetson Nano module

- > 128-core NVIDIA Maxwell GPU
- > Quad-core ARM® A57 CPU
- > 4 GB 64-bit LPDDR4
- > 16 GB eMMC 5.1
- > 10/100/1000BASE-T Ethernet

### Power

- > Voltage Input: 5 V
- > Module Power: 5 W~10 W

### Environment

- > Operating Temperature: -25 C to 80 C\*
- > Storage Temperature: -25 C to 80 C
- > Humidity: 85% RH, 85°C [non-operational]
- > Vibration: Sinusoidal 5 G RMS 10 to 500 Hz, random 2.88 G RMS, 5 to 500 Hz [non-operational]
- > Shock: 140 G, half sine 2 ms duration [non-operational]

\* See thermal design guide for details

# NVIDIA JETSON NANO MODULE

## TECHNICAL SPECIFICATIONS

GPU	128-core Maxwell
CPU	Quad-core ARM A57 @ 1.43 GHz
Memory	4 GB 64-bit LPDDR4 25.6 GB/s
Storage	16 GB eMMC 5.1
Video Encode	4K @ 30   4x 1080p @ 30   9x 720p @ 30 (H.264/H.265)
Video Decode	4K @ 60   2x 4K @ 30   8x 1080p @ 30   18x 720p @ 30 (H.264/H.265)
CSI	12 (3x4 or 4x2) lanes MIPI CSI-2 D-PHY 1.1
Connectivity	Gigabit Ethernet
Display	HDMI 2.0, eDP 1.4, DP 1.2 (two simultaneously)
PCIe	1x1/2/4 PCIe Gen2
USB	1x USB 3.0, 3x USB 2.0
Others	I <sup>2</sup> C, I <sup>2</sup> S, SPI, UART, SD/SDIO, GPIO
Mechanical	69.6 mm x 45 mm 260-pin SODIMM Connector

**Artemis Karia**  
Instagram: [artemis\\_karia](https://www.instagram.com/artemis_karia)

Learn more at <https://developer.nvidia.com/jetson>

© 2019 NVIDIA Corporation. All rights reserved. NVIDIA, the NVIDIA logo, CUDA, Jetson, Jetson Nano, NVIDIA Maxwell, and TensorRT are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated. ARM, AMBA and ARM Powered are registered trademarks of ARM Limited. Cortex, MPCore and Mali are trademarks of ARM Limited. All other brands or product names are the property of their respective holders. "ARM" is used to represent ARM Holdings plc; its operating company ARM Limited; and the regional subsidiaries ARM Inc.; ARM KK; ARM Korea Limited.; ARM Taiwan Limited; ARM France SAS; ARM Consulting (Shanghai) Co. Ltd.; ARM Germany GmbH; ARM Embedded Technologies Pvt. Ltd.; ARM Norway, AS and ARM Sweden AB. JUL19

